

SToic

CLARITY | INNOVATION | VISION

Stoic Technologies 3MP Starlight IP Dome Camera with 3.6MM Fixed Lens, SD Card Slot, Internal POE, IP66 Weatherproof, Starlight, ONVIF 2.4 Support, WDR, HDR

IPS-D7060W



SPECIFICATIONS:

Model NO.	IPS-D7060W
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	3MP
Effective Pixels	2065(H)*1553(V)
Compression	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focus Length	3.6mm (2.8mm/6mm Optional)
Focus Control	Fixed
Lens Type	Fixed
Pixels	4MP
Night Vision	

Infrared LED	14μ x 18PCS
Infrared Distance	20M (65 Feet)
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Internal POE Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2048*1536@30fps
Main Stream 2	1920*1080@30fps
Main Stream 3	/
Sub Stream 1	720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Starlight	Yes
Corridor Pattern	Support
Defog Mode	Support
ROI	/
BLC	Support
HDR	Support
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone

Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands
Interface	
Audio	Optional
Alarm	/
SD Card Slot	Yes
RS485	/
General	
Housing	Metal , IP66
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 850mA
Dimension	87(W) x 75(H) x 87(D)mm
Weight	400g
Compatible Mounting Options: IPSW-JB300 Deep Base Junction Box IPSW-DB200 Deep Base WM-D5900 Wall Mount Bracket www.stoiccctv.com	