

STOiC IP	IPSW-1200
Camera	
Image Sensor	1/1.7" SONY Low Illumination CMOS Sensor
Resolution	4072 X 3046
Compression	H.264/H.265/JPEG/AVI/MJPEG
Lens	
Focus Length	Board Lens 1.77mm/F2.4
Verifocal / Fixed	Fixed
Night Vision	
Infrared LED	42μ x 3PCS
IR Range	20m
Auto Control IR LED	CDS Auto Control (IR Cut Filter)
Camera Features	
OSD Menu	Yes
WDR	Yes
UTC	With supported DVRs.
Noise Reduction	3DNR
Day / Night	Yes
Compatibility	AHD, TVI, CVI, and SD Analog (4-in-1)
Network	
Ethernet	RJ45 1/100Base-T
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Yes. ONVIF 2.4
P2P	Yes, QR Code
Video Delay	0.3s within LAN
Smartphone	iPhone, iPad, Android, Android Pad
General	
Audio	2-way
SD Card Solt	64GB Micro SD
IR Cut Filter	Yes
Power	DC12V 950mA
Dimension	120mm x 49mm
Weight	500g

