

STOiC 4-In-1 Technology	SAS-XVR3200
XVR	
Main Processor	HI3520DV200
Operating System	Embedded LINUX
Video	
Input	Analog HD: 32*1080N Analog HD+Network: 30*Analog(1080N)+2*network(Max 8MP), 28*Analog HD(1080N)+4*network(Max 8MP), 26*Analog HD(1080N)+6*network(Max 8MP), 24*Analog HD(1080N)+8*network(Max 8MP), 22*Analog HD(1080N)+10*network(Max 8MP), 20*Analog HD(1080N)+12*network(Max 8MP), 18*Analog HD(1080N)+14*network(Max 8MP), 16*Analog HD(1080N)+16*network(Max 8MP) 14*Analog HD(1080N)+18*network(Max 8MP), 12*Analog HD(1080N)+20*network(Max8MP), 10*Analog HD(1080N)+22*network(Max 8MP) 8*Analog HD(1080N)+24*network(Max 8MP), 6*Analog HD(1080N)+26*network(Max 8MP), 4*Analog HD(1080N)+28*network(Max 8MP) 2*Analog HD(1080N)+30*network(Max 8MP) Network: 32*network(Max 8MP)(Total incoming bandwidth ≤160M)
Signal Type	Analog / AHD / CVI / TVI 2.0 / IP
Output	1 HDMI, 1 VGA, 1 CVBS
Audio	
Input	12 Channel, RCA
Two-way Audio	No
Output	1 Channel, RCA
Alarm	
Sensor Input	16 Channel
Output	4 Channel
Motion Detection	32 Channel
Trigger Events	Recording, Email, Screen tips, Buzzer
Email Alarm	Send image to designated email
PTZ	
Interface	RS458
Protocol	Pelco-D, Pelco-P
Baud Rate	110-921600
Address	0 - 255
Recording	
Video Compression	H.264
Audio Compression	G.711u
Resolution	960x1080
Record Mode	Manual / Timer/ Motion Detection / Alarm

Network	
Interface	1 RJ45 10M/100M/1000M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4,IPv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP, FTP, UPNP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1~15fps)
Smart Phone	iPhone, ipad, Android ,Android pad
Hard Disk Driver	
Interface Type	8 SATA Interface
Capacity	8 SATA Hard Disk Interface (3.5" SATA, Up to 48TB) + 1 E-SATA Interface (Up to 6TB)
General	
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power Consumption	AC 115~230v ≤35W (Without HDD)
Dimension	17.3 x 17.7 x 3.7

