

STOIC

CLARITY | INNOVATION | VISION

STOIC Technologies 5MP Starlight Turret Dome Camera,
4 in 1 Switchable, 4MP/5MP Switchable, 3.6mm Fixed
Lens, IP66, 80' IR, Defog, Smart IR

STH-D5M61W







SPECIFICATIONS:

Model NO.	STH-B5M61W
Video Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps; CVI: 4M/2M@30fps
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	5MP
Effective Pixels	5M:2592*1944 4M:2560*1440
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s, 1/30s~1/60,000s
S/N Ratio	≥50dB
Scanning System	Progressive Scan
Lens	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	6M Pixels
Auto Iris Support	NO
Night Vision	
Infrared LED	14μ x 18PCS
Infrared Distance	25M (80 Feet)
IR Power On / Off	Smart IR control
Camera Features	
Starlight	/

Day/Night	YES
OSD Menu Language	YES
White Balance	AUTO / MANUAL
Gain Control	AUTO
Noise Reduction	3DNR
Picture Adjustment	YES
WDR	YES
OSD Support	YES
UTC	YES
Dip Switch	/

General

Housing	Metal, IP66
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Audio	/
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	φ93 x 74(H) mm
Weight	400g



Compatible Mounting Brackets:

MB-1061 Deep Base Junction Box
WM-D5500 Wall Mount Bracket

www.stoiccctv.com