STOIC

STH-B5571AFW Stoic 8MP / 5MP Starlight HD Bullet Camera with 2.7-13.5mm Motorized Zoom Lens, IP67 Weatherproof, 4 in 1, UTC, OSD, 131' IR Night Vision



8MP / 5MP

| SPECIFICATION | |
|--------------------|--|
| Model NO. | STH-B5571AFW |
| Video Output Mode | AHD: 8M@15fps, 5M@20fps/12.5fps, 4MP@30fps/25fps/15fps; 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps |
| Camera | |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS sensor |
| Image Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | AUTO / MANUAL |
| Scanning System | Progressive Scan |
| Lens | |
| Focus Length | 2.7-13.5mm |
| Focus Control | Auto |
| Lens Type | Motorized |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 42μ x 4PCS |
| Infrared Distance | 40M |
| IR Power On / Off | AGC Auto Control |

| Camera Features | |
|-----------------------|--------------------------|
| Starlight | YES |
| Day/Night | YES |
| OSD Menu | YES |
| WDR | YES |
| итс | YES |
| Noise Reduction | 3DNR |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |
| General | |
| Housing | Metal, IP67 |
| Bracket | YES |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 750mA |
| Dimension | 211(W) x 92(H) x 90(D)mm |
| Weight | 1400g |