



STH-D5M88AFW Stoic 8MP/5MP Starlight
HD Turret Dome with Motorized Zoom
2.7-13.5mm Lens, 80' IR Night Vision, IP67
Weatherproof, 4 in 1 Support, UTC



8MP / 5MP

SPECIFICATION

Model NO.

STH-D5M88AFW

Video Output Mode

AHD: 8M@15fps, 5M@20fps/12.5fps, 4MP@30fps/25fps/15fps; 2M@30fps/25fps;
CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps;
TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps

Camera

Image Sensor

1/2.8" SONY Starvis Back-illuminated CMOS sensor

Image Resolution

8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080

TV System

PAL/NTSC

Minimum Illumination

0.002 Lux

Scanning System

Progressive Scan

Lens

Focus Length

2.7-13.5mm

Focus Control

Auto

Lens Type

Motorized

Night Vision

IR Cut Filter

YES

Infrared LED

42μ x 2PCS

Infrared Distance

25M (80 Feet)

IR Power On / Off

AGC Auto Control

Camera Features

Starlight	YES
Day/Night	YES
OSD Menu	YES
WDR	YES
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

General

Housing	Metal, IP66
Bracket	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 750mA
Dimension	Φ 119 x 98(H) mm
Weight	800g