

STOIC

CLARITY | INNOVATION | VISION

STOIC Technologies 5MP Starlight HD
Turret Dome with 2.8-12MM Manual Zoom
Lens, 100IR, 4 in 1 Switchable, IP66

STH-D5M90W





SPECIFICATIONS:

Model NO.	STH-D5M90W
Video Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps; CVI: 4M/2M@30fps
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	5MP
Effective Pixels	5M:2592*1944 4M:2560*1440
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
S/N Ratio	≥50dB
Scanning System	Progressive Scan
Lens	
Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Varifocal
Pixels	5M Pixels
Auto Iris Support	NO
Night Vision	
Infrared LED	14μ x 24PCS
Infrared Distance	30M (100')
IR Power On / Off	Smart IR control
Camera Features	
Starlight	YES



Day/Night	YES
OSD Menu Language	YES
White Balance	AUTO / MANUAL
Gain Control	AUTO
Noise Reduction	3DNR
Picture Adjustment	YES
WDR	YES
OSD Support	YES
UTC	YES

General

Housing	Metal, IP66
Bracket	NO
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Audio	/
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 800mA
Dimension	∅ 119 x 98(H) mm
Weight	800g



STH-D5M90W



Compatible Mounting Options:

IPSW-JB300 Junction Box / Base
IPSW-DB200 Deep Base
WM-D5900 Wall Mount Bracket
STC-100W Wall Mount Bracket

www.stoiccctv.com