



TA-V5TVV6TQ

5MP Dome Camera



KEY FEATURES

- 1/2.9" SONY 6MP CMOS Sensor
- Support 4-IN-1
(TVI 5MP / AHD 4MP / CVI 4MP / CVBS 1200TVL)
- 2.8~12mm Varifocal Lens
- 18IR (60ft)
- Low Illumination
- TDN, DWDR, DNR, UTC, OSD
- Vandal Proof & Weather Proof
- DC12V / AC24V (Dual Voltage)

DIMENSIONS



ACCESSORIES



TA-WM-J280 (B280)
Wall Bracket w/
junction box



TA-WM-181 (AB181)
Wall Mount



TA-CM-C300 (B300A)
Ceiling Mount

TA-V5TVV6TQ	
Image Sensor	1/2.9" SONY 6MP CMOS Sensor
Resolution	5MP
Effective Pixels	5M: 2592 x 1944 / 4M: 2560 x 1440
Signal System	NTSC / PAL
Lens	2.8~12mm Manual Zoom Lens
Day & Night	ICR
Minimum Illumination	0.001Lux / F1.2
S/N Ratio	More than 50dB
Synchronous System	Internal
Video Frame Rate	TVI : 5M@20fps/12.5fps, 4M@30fps/15fps; AHD: 4M@30fps/15fps; CVI: 4M@30fps; CVBS: 1200TVL@30fps
Video Output	TVI / AHD / CVI / CVBS (Analog HD)
D/N Mode	Auto / Color / BW (Black and White)
White Balance	ATW / MWB
BLC	Support
IR Distance	60 ft
IR Power On	Photodiode AUTO Control
Power Supply	DC12V / AC24V
Weather Proof	IP66
Dimensions (mm)	Ø139 x 122 (H) mm
Weight (g)	800
Operating Conditions	-10° to 50°C RH95% MAX