

TI-NC408-VDZ

8MP 4K Motorized Zoom IR Dome Camera



KEY FEATURES

- 1/2.5" Sony CMOS Sensor
- 4K resolution 3840 x 2160P
- Low Illumination 0.01 Lux
- Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT, D-WDR, Mirror, Rotate, Defog
- OSD, Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 dual stream media server
- Easy to use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Lightning protection 4000V
- Strong water-proof housing IP66
- 24 pcs SMD IR Led, IR distance 20-30 meters
- HD 3.3-12mm AF lens

TI-NC408-VDZ			
Camera	Image Sensor	1/2.5" Sony CMOS	
	Effective Pixels	8MP	
	Electronic Shutter	AUTO, 1/25s ~ 1/100,000s	
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0 Lux IR on	
	Day/Night	Auto / Color / B/W / Timing	
	WDR	Digital WDR	
	White Balance	Auto / Manual	
	BLC/HLC	Support	
	DNR	2D / 3D DNR	
	Other	AGC, Motion Detection, Privacy Mask, Flip, Rotate, RIO, OSD overlay	
Encode	Embedded Solution	Hi3516A	
	Video Standard	H.264 / H.265	
	Video Resolution	MainStream:15fps@8MP(3840x2160),30fps@6MP(3072x2048)/	
		5MP(2592x1944)/4MP(2592x1520)/3MP/1080P/720P,etc.	
		Sub stream: 720x480/VGA(640x480)/360P/QVGA@30fps,etc.	
	Video Bitrates	512Kbps ~ 12Mbps, VBR/CBR	
	Audio Standard	G.711-u / G.711-a	
OSD Overlay	Title and Time Overlay, custom color adjustable		
IR	IR LED	24 pcs SMD IR LED	
	IR Distance	20-30m	
Lens	Focal Length	3.3-12mm AF Lens	
Options	Optional Function	PoE, Audio	
Network Services	Protocol	HTTP / RTSP / FTP / NFS / SMTP / DHCP / NTP, etc.	
	P2P	Yes	
	Web	IE, Firefox 32bit ESR	
	Media	CMS, Android, IOS	
	ONVIF	17.06 compatible	
General	Network Port	1-RJ45, 100Mbps, PoE optional	
	Power Supply	12VDC±10%	
	Power Consumption	<10 W	
	Operating Conditions	-20 °C ~ +60 °C, 10%~90%RH	

DIMENSION

