

TI-NC405-3VBZ

5 MP UHD IR Dome 4X Motorized Lens IP Camera



KEY FEATURES

- 1/2.8" Sony IMX335 Low light CMOS sensor
- Max. 5MP resolution 2592 x 1944 output
- low illumination 0.01Lux
- Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror, Flip
- RTSP and Onvif 17.06 compatible
- H.265/H.264 dual-stream media server
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 4pcs Array IR Leds, IR distance 210ft
- HD 2.8-12mm AF lens



TI-NC405-3VBZ		
Camera	Image sensor	1/2.8" Sony IMX335 CMOS
	Effective Pixels	2592(H)×1944 (V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	WDR	Digital WDR
	White Balance	Auto
	Other	AGC,2/3 DNR,Motion Detection, Privacy Mask, Mirror, Flip
	Video Standard	H.265/H.264
	Video Resolution	MainStream: 15fps@5MP(2592x1944),25fps@4MP/3MP,30fps@1080P/720P Sub stream: D1/VGA(640x480)/360P/QVGA@25fps
	Video Bitrate	512Kbps - 6Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
	IR LED	4 Array IR Led
Network Services	IR Distance	210ft
	Focal Length	2.8 – 12mm
	Protocol	RTSP/FTP/DHCP/DDNS/NTP/SMTP/NFS
	P2P	Yes
	Web	IE , firefox 32bit ESR
	Media	CMS, Android, iOS
General	ONVIF	17.06 compatible
	Network Port	1-RJ45, 100Mbps, POE
	Power Supply	12 VDC ± 10%
	Power Consumption	< 5 W
	Operating Temp	-22°F – 140°F

DIMENSIONS

