

TI-NC405-PIR

5MP IP Hidden IR Camera with PoE



KEY FEATURES

- 1/3" UHD CMOS sensor
- Max. 5MP resolution 2592x1944
- Low Illumination 0.1Lux
- Day/Night(ICR), AWB, 2D/3D-DNR, IR-CUT, WDR
- RTSP and ONVIF 2.6 compatible
- H.265/H.264 Dual-stream Media Server
- Easy-to-use P2P Cloud Service
- Multi web browser, PC Client, Mobile APP remote access
- Lightning Protection 4000V
- Strong water-proof housing IP66
- Support PoE
- 12 pcs IR LEDs, IR distance 10-15m
- 3.7mm Pinhole Fixed Lens

TI-NC405-PIR		
Camera	Image Sensor	1/3" CMOS
	Effective Pixels	2688(H) x 1520(V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100,000s
	Min. Illumination	0.1Lux@F1.2(AGC ON), 0 Lux with IR
	Day / Night	Auto / Color / BW / Timing
	WDR	Digital WDR
	White Balance	Auto
	AGC / BLC	Support
	DNR	2D/3D DNR
	Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
	Video Standard	H.265 / H.264
	Video Resolution	Main Stream: 15fps@5MP (2592x1944), 20fps@4MP (2592x1520), 25fps@3MP / 1080P / 720P Sub Stream: VGA (640x480) / 360P / QVGA@25fps, etc.
	Video Bit Rate	32Kbps - 8Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
IR LED	IR LED	12 pcs IR LEDs
	IR Distance	10-15m
Lens	Focal Length	3.7mm Pinhole Fixed Lens
Optional	PoE, Audio, etc.	
Network Services	Protocol	HTTP / RTSP / FTP / NFS / SMTP / DHCP / NTP, etc.
	P2P	Yes
	Web	IE, Firefox 32bit ESR
	Media	CMS, Android, IOS
General	ONVIF	2.6 compatible
	Network Port	1-RJ45, 100Mbps, PoE optional
	Power Supply	12VDC ±10%
	Power Consumption	< 5W
	Operating Temperature	-30°C to +60°C, 10%-90%RH