

TI-NC405-VBZ

5MP UHD Motorized IP Camera



KEY FEATURES

- 1/3" UHD CMOS sensor
- UHD resolution 2592 x 1944P
- Low Illumination 0.1 Lux
- Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT, D-WDR, Mirror, Defog
- OSD, Motion detection, Privacy Mask
- RTSP and Onvif 2.6 compatible with many third-party NVR
- H.264 / H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Lightning protection 4000V
- Strong water-proof housing IP66
- 3 pcs High Power Array IR LED, IR distance 40-50m
- HD 2.8-12mm AF lens

TI-NC405-VBZ		
Camera	Image Sensor	1/3" Sony CMOS
	Effective Pixels	5MP
	Electronic Shutter	AUTO, 1/25s ~ 1/100,000s
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0 Lux IR on
	Day/Night	Auto / Color / B/W / Timing
	WDR	Digital WDR
	White Balance	Auto / Manual
	BLC/HLC	Support
	DNR	2D / 3D DNR
	Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror
Encode	Video Standard	H.264 / H.265
	Video Resolution	MainStream: 15fps@5MP(2592x1944), 20fps@4MP(2592x1520), 25fps@3MP/1080P/720P
		Sub stream: VGA/360P@25fps, etc.
	Video Bitrates	32Kbps ~ 8Mbps, VBR/CBR
	Audio Standard	G.711-u / G.711-a
	OSD Overlay	Title and Time Overlay
IR	IR LED	24 pcs SMD IR LED
	IR Distance	40-50m
Lens	Focal Length	2.8-12mm AF Lens
Options	Optional Function	PoE, Audio
Network Services	Protocol	HTTP / RTSP / FTP / NFS / SMTP / DHCP / NTP, etc.
	P2P	Yes
	Web	IE, Firefox 32bit ESR
	Media	CMS, Android, IOS
	ONVIF	2.6 compatible
General	Network Port	1-RJ45, 100Mbps, PoE optional
	Power Supply	12VDC±10%
	Power Consumption	<10 W
	Operating Conditions	-20 °C ~ +60 °C, 10%~90%RH

DIMENSION

