

TI-NC405-VDZ

5MP UHD IP IR Vandal-proof Dome Camera



KEY FEATURES

- 1/2.9" Sony IMX326 CMOS sensor
- UHD resolution 2592 x 1944P
- Low illumination 0.05Lux
- Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT, D-WDR, Mirror, Rotate, Defogging
- Multiply Style OSD Overlay, Motion Detection, Privacy Mask
- RTSP and ONVIF 2.6 compatible with many third-party NVR
- H.264/H.265
- Easy to use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to email and FTP, NFS, NAS video storage
- Lightning protection 4000V
- Strong waterproof housing IP66
- IR distance 20-30m
- HD 2.7-13.5mm VF lens

TI-NC405-VDZ		
Camera	Image Sensor	1/2.9" 6.82MP CMOS
	Effective Pixels	3096(H) x 2196(V)
	Electronic Shutter	auto, 1/25S ~ 1/100,000s
	Min. Illumination	0.05 lux@(F1.2, AGC ON), 0 lux with IR
	Day / Night	Auto / Color / B/W / Timing
	WDR	Digital WDR
	White Balance	Auto / Manual
	BLC	Support
	DNR	2D / 3D DNR
	Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
Encode	Video Standard	H.264 / H.265
	Video Resolution	Main Stream: 18fps@5MP (2592x1944), 25fps@4MP (2592x1520), 30fps@3MP / 1080P / 720P, Sub Stream: VGA / 360P@30fps, etc.
	Video Bit Rate	32 Kbps ~ 8 Mbps, VBR/CBR
	Audio Standard	G.711-u / G.711-a
	OSD Overlay	Title and Time overlay
IR	IR LED	24 pcs SMD IR LED
	IR Distance	20-30m
Lens	Focal Length	2.7-13.5mm AF Lens
	Zoom	4x Optical Zoom
Optional	Function	PoE, Audio, Gray Housing
Network Services	Protocol	HTTP / RTSP / FTP / NFS / SMTP / DHCP / NTP, etc.
	P2P	Yes
	Web	IE, Firefox 32bit ESR
	Media	CMS, Android, IOS
	ONVIF	2.6 compatible
General	Network Port	1-RJ45, 100Mbps, PoE optional
	Power Supply	12VDC $\pm$ 10%
	Power Consumption	< 8W
	Operating Temperature	-20°C to +60°C, 10%-90%RH

DIMENSION

