

THK-NC324MB

4MP IR Fixed Bullet Network Camera



KEY FEATURES

- ◆ 1/3" Progressive Scan CMOS
- ◆ 2560 x 1440 @ 30fps
- ◆ 4mm Fixed Lens
- ◆ Color: 0.01Lux @ (F1.2, AGC ON), 0.018 Lux @ (f1.6, AGC ON), 0 Lux with IR
- ◆ H.265+, H.265, H.264+, H.264
- ◆ Three streams
- ◆ 120dB WDR
- ◆ 2 Behavior analyses and face detection
- ◆ BLC / 3D DNR / ROI
- ◆ IP67
- ◆ Built-in micro SD/SDHC/SDXC card slot, up to 128GB
- ◆ 3-Axis adjustment

ACCESSORIES (optional)



1280ZJ-XS
Junction Box

THK-NC324MB	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Speed	1/3s to 1/10,000 s
Slow Shutter	Yes
Auto-Iris	No
Day & Night	IR cut filter
Digital Noise Reduction	3D DNR
WDR	120dB
3-Axis Adjustment	Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°
Lens	
Focal Length	4 mm
Aperture	F1.6
Focus	Manual
FOV	4mm: horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 93°
Lens Mount	M12
IR	
IR Range	Up to 30m
Wavelength	850nm
Compression Standard	
Video Compression	Main stream: H.265 / H.264 Sub-stream: H.265 / H.264 / MJPEG Third stream: H.265 / H.264
H.264 Type	Main Profile / High Profile
H.264+	Main stream and sub-stream support
H.265 Type	Main Profile
H.265+	Main stream and sub-stream support
Video Bit rate	32 Kbps to 16 Mbps
Smart Feature-set	
Behavior Analysis	Line crossing detection, intrusion detection
Face Detection	Yes
Region of Interest	1 fixed region for main stream and sub-stream
Image	
Max. Resolution	2560 x 1440
Main Stream	50Hz:25fps (2560x1440, 2304x1296, 1920x1080), 60Hz:30fps (2560x1440, 2304x1296, 1920x1080)
Sub Stream	50Hz:25fps (640x480, 640x360, 320x240) 60Hz:30fps (640x480, 640x360, 320x240)
Third Stream	50Hz: 25fps (1280x720, 640x360, 352x288) 60Hz: 30fps (1280x720, 640x360, 352x240)
Image Enhancement	BLC/3D DNR
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser
Day / Night Switch	Auto / Schedule

THK-NC324MB

4MP IR Fixed Bullet Network Camera



THK-NC324MB

Network	
Network Storage	Support Micro SD/SDHC/SDXC card (128G), Local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP,PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users; 3 levels: Administrator, Operator and User
Web Browser	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Video Output	No
On-board storage	Built in Micro SD/SDHC/SDXC slot, up to 128GB
SVC	H.264 and H.265 encoding
Reset Button	Yes
General	
Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), Humidity 95% or less (non-condensing)
Power Supply	12VDC ± 25%, Φ 5.5mm coaxial power plug, PoE (802.3af, class 3)
Power Consumption	12VDC, 0.5A, max. 6W
Current	PoE (802.3af, 37V to 57V), 0.2A to 0.1A, max. 7.5W
Protection Level	IP67 TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection
Material	Metal
Dimensions	Camera: Φ 70 x 155.03mm (Φ 2.8" x 6.1") Package: 216 x 121 x 118mm (8.5" x 4.8" x 4.7")
Weight	Camera: Approx. 420g (0.9lb.) With Package: Approx. 700g (1.5lb.)

DIMENSION

