

TI-POE8GF-120

8 Ports PoE Ethernet Switch



FEATURES

- ◆ Conforms to IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.3at
Provide 8 PoE 10/100 Base-TX ports, including 1Gbps Uplink Port
- ◆ Provide 1 SFP Port (100Mbps) and 1 SFP Port (1Gbps)
- ◆ IEEE802.3x Flow control
- ◆ Surge protection for each port
- ◆ Max. 15W per port (Total 120W)
- ◆ 48VDC Power Supply

SPECIFICATIONS

Item			Description
Power Supply			External Power Adaptor
Voltage Range			DC48V ~ 52V
Consumption			<6W
Speed			1-8 port: 10/100Mbps ; 1 Uplink: 1000Mbps
Transmission Distance			1-8 port 100m with 100 Mbps ; Uplink: 1 Gigabit Combo and 1 Gigabit SFP
Ethernet Standard			IEEE 802.3, 802.3u, 802.3af/at
Switching capacity			9.6G
Transfer Rate			14,880 pps for 10Mbps / 148,800 pps for 100 Mbps
MAC Address			4K MAC address table
Working Temperature			0° ~ 40° C
Storage Temperature			-40° ~ 70° C
Humidity Non-condensing			0 ~ 85%
Dimension L X W X H			218mm x 107mm x 29mm
Color			Gray
G1,G2 Combo	ON	Green	The port is connected
LINK/ACT	On	Green	The port is connected
	Blinks	-	The port is receiving or transmitting data
	Off	-	The port is not linked successfully with the device
PoE (Powered by 45.78)	On	Orange	Power is being distributed
	Off	-	Power is not being distributed

Application

