

Ethernet Switches

NSW2010-24T2GC-POE-IN



Features

- Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Specifications

Model	NSW2010-24T2GC-PoE-IN
Hardware Specification	
Ports Type	24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Switching capacity	8.8 Gbps
Packet Buffer	4 M bit

Forwarding performance	6.55Mpps
MAC	16K
Max.Power	390W
Weight	<4.2 kg
Cooling Fans	2
Mean Time Between Failure (MTBF)	> 50000 hours
Dimensions (W×D×H)	440mm x 207mm x 45mm(17.3"×8.1"×1.8")
Operating humidity	10%~90% (non-condensing)
Working Mode	Default (Normal mode) : All ports can communicate with each other, EXTEND (Surveillance mode): Transmission distance up to 250 meters, VLAN (Secure mode): Downlink ports can communicate only with uplink ports.

Ordering Info

Product Model	Description
NSW2010-24T2GC-PoE-IN	Ethernet Switch(PoE)

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.