



# TA-AC326-FD4M

## 5MP Turret Camera



### KEY FEATURES

- 5MP High-performance CMOS
- 2560 x 1944 resolution
- 2.8mm Fixed Focal Lens
- EXIR 2.0, smart IR, up to 40m IR distance
- OSD Menu, 2D-DNR, DWDR
- 4 in 1 Video Output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the Coax

TA-AC326-FD4M	
Image Sensor	5MP CMOS Image Sensor
Resolution	2592 (H) x 1944 (V)
Min. Illumination	Color: 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25s to 1/50,000s NTSC: 1/30s to 1/50,000s
Lens	2.8/3.6/6.0mm
Horizontal Field of View	85.5° (2.8mm), 80.1° (3.6mm), 57.1° (6mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°; Tilt: 0° to 75°, Rotate: 0° to 360°
Synchronization	Internal synchronization
Frame Rate	PAL: 5MP@20fps, 4MP@25fps, 1080p@25fps NTSC: 5MP@20fps, 4MP@30fps, 1080p@30fps
Video Output	1 HD analog output
White Balance	ATW/MWB
BLC	Support
Functions	Brightness, Sharpness, Digital Noise Reduction, Mirror, Bad pixel correction, Smart IR
Operating Conditions	-40° to 60°C (-40°F to 140°F)/ Humidity: 90% or less (non-condensing)
IR Distance	Up to 40m
Protection Level	IP67
Material	Enclosure: Plastic / Main Body: Metal
Power Supply	12VDC±25%
Communication	Up the coax
Dimension (mm)	Φ110mm x 93.2mm (Φ4.33" x 3.67")
Weight (g)	350g (0.77 lb.)