

## POE-1PG Specifications:



No. of Ports	1
Pass Through Data Rates	10/100/1000 Mbps
Power over Ethernet Output	Pin Assignment and Polarity:4/5 (+), 7/8 (-) Output Power Voltage: 55Vdc User Port Power: 20W
Input Power Requirements	AC Input Voltage: 100 to 240 Vac AC Input Current: 0.2A 100-240 Vac AC Frequency: 50 to 60 Hz
Dimensions	150mmx65mmx38mm
Weight	

Indicators	System Indicator: AC Power User Indicator: Channel Power
Connectors	Shielded RJ-45, EIA 568A and 568B
Environmental Conditions	Operating Ambient Temperature:-10 to 45°C Operating Humidity:Maximum 90%, Non-condensing Storage Temperature:-20 to 70°C Storage Humidity:Maximum 95%, Non-condensing
Reliability	MTBF: 100,000 hrs. @25°C
Regulatory Compliance	IEEE 802.3af (PoE), RoHS Compliant, CE, FCC
Electromagnetic Emission & Immunity	FCC Part15, Class B EN 55022 Class B (Emissions) EN 55024 (Immunity), VCCI
Surge Protection	AC port: 6kV RJ45 port: 4kV
Safety Approvals	UL/cUL Per EN 6095-1 GS Mark Per EN 60950-1