

2MP IR Smart Pan & Tilt Camera

T1L-2WT



Key Features

- Easy to install and use.
- Clear and smooth video browsing; intelligent transmission giving full play to capabilities of the network.
- Online firmware upgrade, and synchronous updating of the functions and experience.
- Two-way voice intercom supported; echo eliminated; noise suppressed.
- Remote real-time monitoring supported with Android and IOS intelligent terminal.
- Lighting for infrared night vision; 24h around-the-clock monitoring; IR-CUT switching; free of color cast in the daytime; clearer night vision.
- Intelligent push to filter out useless information.
- QR code intelligent connection and network allocation supported.
- Supporting human contour detection, activity zone, intelligent push and pet snapshot.
- Small and exquisite appearance, various colors.

Specifications

	T1L-2WT
Camera	
Sensor	1/3" color CMOS sensor, 2.0 megapixel.
Lens	3.6mm@F2.0

Angle of View	H (horizontal) 85°; V (vertical) 48°; D (diagonal) 100°.
Minimum Illumination	0.01Lux
IR Range	Up to 10m IR range
Audio	
Input / Output	Two-way voice intercom available (built-in Microphone and speaker).
Video	
Video Compression	H.265
Lighting frequency	50Hz, 60Hz
Image frame rate	15fps
Network	
Protocols	TCP/IP, UDP/IP, DHCP, RTMP, MUDP
Wireless Network	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna.
IP Address Supported	Dynamic IP address supported.
Interface	
Power Supply	1 Micro USB interface, DC 5V/1A
SD card	1 Micro SD card slot
Keys	1 function key
Storage	
Cloud storage	supported
SD card storage	Supported (up to 128 GB)
Intelligent functions	
Intelligent push	supported
Pet detection	supported
Vehicle detection	supported
Human contour detection,	supported
Motion detection	supported
Motion tracking	supported
Humanoid tracking	supported
Alarm	
Alarm linkage	Support video recording, sound alarm.
Alarm notification	Alarm push by mobile APP.
General	
Install method	Ceiling or wall mounted
Dimensions (L × W × H)	72 × 72 × 115mm
Weight	180g
Working Environment	-10° ~ 45°C /10% ~ 80% (no condensation)
Storage Environment	-20°C ~ 60° /0% ~ 90% (no condensation)
PTZ	H (horizontal) 0° ~ 355°; V (vertical) -20° ~ 90°
LED indication	Monochrome white light (power/network signal/function indicator).

Dimensions

