Akuvox NS-2

Datasheet

Another choice for old building retrofit

The NS-2 is Akuvox 2-wire IP network switch which provides a convenient way to upgrade analogue intercom systems, no need for rewiring. Its super long transmission distance & good compatibility with existing lines makes it fit for most of old buildings.

At a Glance

- Support network and power supply for R20A-2 or C313W-2 through 2-wire cable;
- Support multi-level cascade through 2-wire cable;
- Connects up to 6 pcs of Akuvox 2-wire IP intercom devices;
- Super long transmission distance via 2-wire cable;
- Powerd by 48VDC or 24VDC power supply unit;
- Rail mounting installation;

Physical & Power

- Communication: TCP/IP
- RJ45 port: 1 x RJ45 port, 10/100Mbps adapter
- 2-wire ports: 6 pair
- Working voltage: 48V or 24V
- Status Indicator: 4
- Installation: Rail mounting

- Working temperature: -20C°~+50C°
- Storage temperature: -20C°~+70C°
- Working humidity: 10%~90%
- Dimension: 161 x 90 x 65 (mm)

Physical & Power

• Old building retrofit



10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com

Model:NS-2		Power
CE Z	Akuvox Open A Smart World	Host
		Slave
		Network