



STH-B5588AFW

Stoic 5MP/8MP Lite Starlight HD Bullet Camera with 2.7-13.5mm Motorized Zoom, 120IR, IP67, NDAA Compliant

SPECIFICATION

Model NO.	STH-B5588AFW
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4MP@30fps/25fps/15fps; 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps
Camera Features	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO / MANUAL
Scanning System	Progressive Scan
Lens	
Focus Length	2.7-13.5mm
Focus Control	Auto
Lens Type	Motorized
Night Vision	
IR Cut Filter	YES
Infrared LED	42 μ x 4PCS
Infrared Distance	40M (120 Feet)
IR Power On / Off	AGC Auto Control
Camera Features	
Starlight	YES

Day/Night	YES
OSD Menu	YES
WDR	YES
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO
General	
Housing	Metal, IP67
Bracket	YES
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 750mA
Dimension	211(W) x 92(H) x 90(D)mm
Weight	1400g