

Electric Automatic Door Opener



VIS-440A-SLIM (Silver)
Inswing Doors

VIS-440B-SLIM (Silver)
Out Swing Doors



VIS-440A-SLIM-BL (Black)
Inswing Doors

VIS-440B-SLIM-BL (Black)
Out Swing Doors

Model No.	VIS-440x-SLIM
Size (LxWxH)	475*81*98mm (18.70*3.19*3.86 In.)
Weight	12.2lbs
Door Weight	Max. 440lbs (200kgs)
Door Width	≤ 1200mm (47.24 inches)
Operation Voltage	AC100V-240V
Door Opening Angle	Max 110°
Active Open Time	3-7s/90°
Ambient Temperature	-20°C~ +55°C (-4°F~ 131°F)
Hold-open Time	0 - 20s (Adjustable)
Protection Class	IP21 (Indoor use only)
Lock Function	Lock with remote/Automatic lock

Features

- 55w high speed dc brushless motor, long service life, low noise.
- In main and slave mode. Sequence will not change because of encounter an obstacle.
- Double gear box design, high speed ratio, high strength, can work with doors up to 440lbs.
- Push and go function.
- The magnetic lock can be connected directly to the controller without the need for additional power supply.
- The controller has added the anti-interference function of the sensor, and the sensor can be directly connected inside and outside the operator.

Items included in the package:

- 100V USA plug Automatic door Opener
- 2 Wireless remotes
- Built-in receiver
- Screw and screw anchors
- Power cord
- Allen wrench M5x50x120
- 25mm and 50mm extensions
- 2 stickers
- Black and white manual
- In swing bracket pull arm
(only VIS-440A-SLIM / VIS-440A-SLIM-BL)
- Outswing bracket push arm
(only VIS-440B-SLIM / VIS-440B-SLIM-BL)



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com

Wireless Keyfob Remote
for Automatic Door
Opener



Model No.	VIS-8016
Power Supply	AC/DC 12~36V
Current of Electric Lock	3A (12V)
Static Power	35mA
Action Current	85mA (Non-current electric lock)
The Interval Time to Open Lock and Auto-door	1s
Professional Appliance	Built-in surge absorber
Transmitting/Receiving Method	Microwave level with a roller code
Remote Con. Battery Using Life	>18000 times
Working Environment Temp.	-42°C ~ 45°C (-43.6°F~ 113°F)
Working Environment Humidity	10~90% RH
Appearance Dimension	123*50*32mm (4.84*1.96*1.25in.)
Total Weight	280g

Wireless Push Button
for Automatic Door Opener



Model No.	VIS-8015
Power Supply	6V (2/pcs 3V battery)
Emission Current	3.9mA
Life of Battery	more than 20000 times
Transmit Distance	More than 25M
Operation Temperature	-42°C ~ 45°C (-43.6°F~ 113°F)
Operation Humidity	10~90% RH
Dimension	203*41*12.5mm (7.99*1.61*0.49in.)

* The VIS-8015 is sold separately.



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com