

STOIC

IPS-PD2DAHSL4X

2MP Mini IP PTZ with 2.8-12mm Motorized Zoom, 130IR, True WDR, IP66, 1/2.9" Sony Low Light Sensor



SPECIFICATION

Model	IPS-PD2DAHSL4X
--------------	-----------------------

Camera

Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.265
Minimum Illumination	Color: 0.008 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR
S/N Ratio	60db
WDR	120dB

PTZ

Horizontal Rotation Speed	25°/S
Horizontal Rotation Range	0°~350°
Tilt Rotation Speed	20°/S
Tilt Rotation Range	0°~70°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points

Lens

Focus Length	2.8mm-12mm
Focus Control	4X Optical Zoom

Night Vision

Infrared LED	∅ 35x4PCS
IR Range	45M
Day-night mode	AUTO

Network

Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support (PROFILE S,PROFILE G,PROFILE T)
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	1920*1080@30fps
Main Stream2	1280*720@30fps
Main Stream3	N/A
Main Stream4	N/A
Main Stream5	N/A
Main Stream6	N/A
Sub Stream1	800*448@30fps
Sub Stream2	704*576@30fps
Sub Stream3	640*360@30fps
Sub Stream4	352*288@30fps

AI Function

Intelligent Analysis	/
----------------------	---

Interface

Audio	/
Audio Encode	G711A, C711U
Alarm	N/A
SD Card Slot	N/A
POE	YES

General

Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -15°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/2A
Lightning Protection	Transient voltage 3000V
Dimension	14x14x13(cm)
Weight	1100g