

6 MP ColorVu Fixed Bullet Network Camera



MODEL **TI-NC406C-MBA/28**



KEY FEATURES

- High quality imaging with 6 MP resolution (3072 x 2048)
- Efficient H.264/265 compression technology
- ICR auto switch, true day / night vision
- 3D DNR, DWDR, HLC, BLC, Defog, NIR
- OSD Overlay, Motion Detection, Privacy Mask
- Easy-to-use P2P Cloud service
- Support Alarm Snapshot to Email
- 100mbps network port, IEEE802.3af PoE
- Support Human Body & Vehicle Detection
- 2 pcs Soft & Warm Supplemental Light Up to 90 ft (25-30m) IR
- 2.8mm Fixed Lens
- DC12V/PoE power
- Water and dust resistant (IP67) and vandal resistant
- Lightning protection 4000V
- Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- Built-in-MIC

TI-NC406C-MBA/28

6 MP ColoVu Fixed Bullet Network Camera

SPECIFICATIONS

| Model | TI-NC406C-MBA/28 |
|--------------------------|---|
| Camera | |
| Image Sensor | 1/2.8" Sony CMOS |
| Min.Illumination | Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR on |
| Effective Pixels | 3072(H) x 2048 (V) |
| Electronic Shutter | AUTO, 1/25s - 1/100000s |
| Day/Night | Auto/Color/(B/W)/Timing |
| Wide Dynamic Range | DWDR |
| White Balance | Auto /Manual |
| AGC/BLC/HLC | Support |
| DNR | 2D/3D DNR |
| Other | Multi-Line OSD, Motion Detection, Privacy Mask, Mirror |
| Lens | |
| Lens Type | 2.8 mm |
| Illuminator | |
| IR Led | 2 pcs Soft & Warm Supplemental Light |
| IR Range | Up to 90 ft (30 m) |
| Encode | |
| Video Standard | H.264/ H.265 |
| Video Resolution | Main Stream: 25 fps @ 6MP (3072 X 2048)/ 5MP(2592 x 1944), Sub Stream: 30 fps @ D1/VGA/360P/CIF, etc |
| Video Bit Rate | 64 Kbps to 8 Mbps, VBR/CBR |
| Audio Standard | G.711-u/G.711-a/AAC |
| Built-in Mic | Yes |
| Smart Event | Human Body & Vehicle Detection |
| Optional Function | |
| | POE, Audio, rtc |
| Network | |
| Protocol | HTTP(S)/RTSP/RTMP/FTP/NFS/SMTP/DHCP/NTP, etc |
| P2P | Yes |
| Protocols | IE, Firefox 32bit ESR, etc |
| Media | CMS, Android, iOS |
| ONVIF | 17.06 Compatible |
| Network | |
| Network Port | 1-RJ45, 100Mbps, POE optionl |
| Power Supply | 12 VDC PoE |
| Power Consumption | < 5W |
| Operating | - 30 °C ~ 60 °C , 10%-90% RH |