

# 4K Colorvu Fixed Mini Bullet Network Camera



MODEL **TI-NC408C-MBA/28**



## KEY FEATURES

- High quality imaging with 6 MP resolution (3840 x 2160P)
- Low illumination 0.01Lux
- Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror
- RTSP and Onvif 17.06 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Internal Microphone, reset button optional
- RJ45 100mbps network port, IEEE802.3af PoE
- SD card slot optional
- Lightning protection 4000V
- Strong water-proof housing, IP67
- 2PCS Soft & Warm Supplemental Light,
- Light distance:25-30M
- HD 2.8mm F1.0 true starlight lens

# TI-NC408C-MBA/28

## 4K Colorvu Fixed Mini Bullet Network Camera

### SPECIFICATIONS

Model	TI-NC408C-MBA/28
<b>Camera</b>	
Image Sensor	1/2.9" IMX 415 Sony Sensor
Effective Pixels	3840 (H) × 2160 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto /Manual
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Motion Detection, Privacy Mask, Mirror, flip
<b>Encode</b>	
Embedded Resolution	Mstar 328Q
Video Standard	H.264/H.265
Video Resolution	Main Stream:20fps@8MP(3840x2160),30fps@6MP(3072x2048)/5MP(2592x1944)/4MP/3MP/1080P/720P,etc. Sub stream: 720x480/VGA(640x480)/360P/QVGA@30fps,etc
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
OSD Overlay	Title and Time overlay
<b>Leds</b>	
Leds	2PCS Soft & Warm Supplemental Light
Light Distance	25-30 M
<b>Lens</b>	
Focal length	HD 2.8mm F1.0 true starlight lens
<b>Optional Functions</b>	
Audio/SD card slot	(support maximum 256GB SD card )
<b>Network Services</b>	
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P	Yes
Protocols	IE , Firefox (32bit esr), etc.
Media	CMS, Android, iOS
ONVIF	17.06 compatible
<b>General</b>	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	IEEE802.3af PoE, 12 VDC ± 10%
Power Consumption	< 8 W
Operating Temp.	-22°F – 140°F, 10% – 90%RH

# TI-NC408C-MBA/28

4K Colorvu Fixed Mini Bullet Network Camera

## DIMENSION

