

6MP Fixed Turret Network Camera



MODEL **TI-NC416-XDA-28**



KEY FEATURES

- High quality imaging with 6 MP resolution
- Efficient H.264/265 compression technology
- ICR auto switch, true day / night vision
- 3D DNR, DWDR, HLC, BLC, Defog, NIR
- OSD Overlay, Motion Detection, Privacy Mask
- 2pcs IR Array Leds, IR distance : 90FT
- 2.8mm Fixed Lens
- DC12V/PoE power
- Water and dust resistant (IP66) and vandal resistant
- Lightning protection 4000V
- Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- Intelligent analytics
- Built in MIC/ SD Card Slot/ Reset Button

TI-NC416-XDA-28

6MP Fixed Turret Dome Network Camera

SPECIFICATIONS

Model	TI-NC416-XDA-28
Camera	
Image Sensor	1/2.8" Sony CMOS
Min.Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR on
Effective Pixels	3072(H) x 2048 (V)
Electronic Shutter	AUTO, 1/25s - 1/100000s
Day/Night	Auto/Color/(B/W)/Timing
Wide Dynamic Range	DWDR
White Balance	Auto /Manual
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Multi-Line OSD, Motion Detection, Privacy Mask, Mirror
Lens	
Lens Type	2.8 mm
Illuminator	
IR Led	18PCS SMD Array
IR Range	Up to 90 ft (30 m)
Encode	
Video Standard	H.264/ H.265
Video Resolution	Main Strem: 25 fps @ 6MP (3072 X 2048)/ 5MP(2592 x 1944), Sub Stream: 30 fps @ D1/VGA/360P/CIF, etc
Video Bit Rate	8 independent 100 Mba 64 Kbps to 8 Mbps, VBR/CBR ps PoE network interfaces
Audio Standard	G.711-u/G.711-a/AAC
Built-in Mic	Yes
Optional Function	
	POE, Audio, rtc
Network	
Protocol	HTTP(S)/RTSP/RTMP/FTP/NFS/SMTp/DHCP/NTP, etc
P2P	Yes
Protocols	IE, Firefox 32bit ESR, etc
Media	CMS, Android, iOS
ONVIF	17.06 Compatible
Network Port	1-RJ45, 100Mbps, POE optioanl
Power Supply	12 VDC PoE
Power Consumption	< 5W
Operating	-22°F ~ 140°F (- 30 °C ~ 60 °C) , 10%-90% RH

TI-NC416-XDA-28

6MP Fixed Turret Dome Network Camera

DIMENSION

