



## **KR702E** ZKAccess Proximity card reader

## KR702E is an IP65-rated weather resistant single-gang ZKAccess proximity card reader.

Due to its convenient single-gang size, KR702E is the ideal card access solution for any metal doors with thin frames, parking gates, fences, turnstiles or any security device having a narrow mounting surface.

KR702E also comes with a keypad which provides users both added security and convenience.

KR702E has a built-in Wiegand-Out port which can be connected to most any access control panel (including ZKAccess C3 and InBio door controllers).

## Specifications

Technology	Proximity
Supported card types	ZKAccess 125 KHz (optional Mifare)
Mounting	Single-gang
Indoor & Outdoor Installation	Electronics sealed in weather and tamper-resistant epoxy potting
Keypad	12 keys (0-9, *, #)
Wiegand Inferface	Wiegand-Out port
Power Supply	12V DC
IP-rating	65
Operating Temperature	32 F to 158 F (0 °C- 70 °C)
Operating Humidity	20% - 80%
Dimensions (H×W×D)	4.4 x 3 x .6 inches (113 x 75 x 16 mm)
Certifications	CE, FCC
Current draw	30 mA typical, 75 mA peak @ 12V DC
Read range	Up to 3 inches (80 mm)

## \*Not to be installed in direct sunlight



1600 Union Hill Road Alpharetta, GA 30005 Phone: (862) 505-2101 | Fax: (862) 204-5906 | info@zktecousa.com | www.zktecousa.com

© Copyright 2023. ZKTeco Inc. ZKTeco Logo and ZKTeco USA Logo have registered trademarks of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.